

**82 grams 2.9 oz**

# Ultralight Hunting Bipod



**NEW!**

**Cant friction lock**



**Adapts to any terrain**  
Cant 20° and pan  
2° left and right  
of center

**Instantly deployable**  
Folded legs  
deploy in a  
split second

# The World's Lightest Fully Functional Bipod

**NEOPOD**  
HUNTING BIPOD



**NEW!**

Cant friction lock

Quick-detach Spigot  
For lowest possible  
center of gravity  
40° tilt - pan 4°



**No drilling, no visit to gunsmith**  
— adapters for all major interfaces and gun makes



Blaser R8/R93  
Success & Professional  
7g .25oz



Sauer 202, 303 & 404  
26g .9oz



Universal sling stud  
33g 1.2oz



Picatinny rail 29g 1oz



Mauser M12 Extreme,  
Impact & Trail. 8g .30z



Silencer 22g .8oz



Vertical flush cup  
to sling stud 6g .2oz



# Made from Carbon Fibre reinforced PEEK, generally regarded as the World's highest performing material

<b>Weight (standard)</b>	<b>82 grams / 2.9 oz</b>
<b>Weight (with cant friction lock)</b>	<b>90 grams / 3.2 oz</b>
<b>Height, minimum:</b>	14.5cm / 5.7" from center of spigot
<b>Height, maximum:</b>	21.5cm / 8.5" from center of spigot
<b>Length of legs retracted:</b>	17cm / 6.7"
<b>Length of legs extended:</b>	24cm / 9.4"
<b>Leg adjustment increments:</b>	7mm / .28"
<b>Leg angle:</b>	55 degrees
<b>Cant:</b>	20 degrees left and right of center
<b>Pan:</b>	2 degrees left and right of center
<b>Construction:</b>	Injection molded Victrex 30% carbon fiber reinforced PEEK composite
<b>Spigot length:</b>	38 mm
<b>Spigot diameter:</b>	7 mm
<b>Adapter material:</b>	Aluminium alloy, stainless steel



**STEINERT**  
**SENSING SYSTEMS**

ENGINEERED TO GIVE YOU AN UNFAIR ADVANTAGE

**Steinert Sensing Systems AS**  
Bogstadveien 27 B, 0355 Oslo Norway

Phone: +47 928 45 303  
Email: [sales@steinertsensing.com](mailto:sales@steinertsensing.com)  
**[www.steinertsensing.com](http://www.steinertsensing.com)**



**NEOPOD**  
HUNTING BIPOD



No drilling, no visit  
to gunsmith  
Adapters for all  
major interfaces  
and gun makes

Lowest possible  
center of gravity  
Maximum stability,  
spigot aligned with  
leg hinges